

Date: _____

Job Name: _____

Location: _____

Purchaser: _____

Installer: _____

Submitted to: _____



Compatibility

For ductless systems. Compatible with all mini-splits, room ACs, window ACs, PTACs, and PTHPs using an infrared remote control with a display.

Power Source

Installation available using 24V-40VA step-down transformer.

Operating Voltage

5V-2A from 24V-40VA

Standby Average Power Consumption

<1W

Time to Enter Network Standby After User Interaction

<1 minute

Static Temperature Accuracy

< ± 1.0° F

Built-In Sensors

Temperature/Humidity

Storage

Temperature: -31° F to 113° F

Operating Temperature

23° F to 122° F

Operating Humidity

5% to 95%

Temperature Setpoint Limit

45° F to 90° F

Radio Parameter

Frequency Band : 2.412 to 2.484 GHz
Maximum Radio-Frequency power : 20 dBm
WLAN Standard : IEEE 802.11 b/g/n
WLAN Channel : 1-11

ProWarranty

Extended 5-year coverage with Automatic warranty registration, ensuring peace of mind and long-term protection for your customers.


Compatible with All Ductless AC Brands




& many more




→ What's in the Box?




Boldr Smart Controller



ProMount
Hardwired Wall Mount
Requires 2-3/8" hole saw.



LiteMount
Snap Wall Mount



LiteStand

Power cable

PowerBrick

US, EU, AU plugs

→ Product Dimensions

